



PLUG-IN Line



Rail



Operation: POWER
Inlet plug 16A - 230V
Outlet socket 16A - 230V



4x320W LED - 8,5M





4x320W LED - 8,5M













FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 8,5 meters vertical tower, 340° rotatable
- Manual lifting system by winch complete with auto-braking system
- · Galvanized metalworks
- 80 µm powder coating
- Very compact dimensions, up to 22 units per truck
- Sites forklift pockets
- Top and sides forklift pockets for effective handling
- Guided main coiled cable to avoid damage during tower operation
- · Circuit breaker for electrical protection against overload
- Certified wind stability up tp 110 km/h
- 4 extendable & height adjustable stabilizers
- Inlet plug and outlet socket to connect in series more units



EASY















Dimensions & weight	Dimensions min (mm)				Dimensions max(mm)			Total weight (kg)		
	1100x1100x2650 (LxWxH)				2360x2360x8500 (LxWxH)			445		
Floodlights	Туре	Power (each)		Floodlight	Floodlights number		Illuminated area (sqm)		Options	
	Led	320W 4		4		65	9300		Light sensor	
Mast	Lifting method		Max Height		Max Wind Speed			Rotation		
	Manual		8,5 m		110 km/h			340°		
Input&output	Inlet plug				Outlet so	Outlet socket				
	16A - 230V				16A - 23	16A - 230V				

