



art. 8034 LITTLE-LORD/CR

Mod	CR	Installation	Indoor and outdoor floodlight
Material	Die cast aluminium body, painted with polyester coated anticorrosion powder anthracite color, tempered transparent glass mm 5 thickness, silicon gasket	Insulation class	Class I
Protection index	IP66	Impact degree	IK08
Color rendering index (CRI)	> 80	Ambient temperature (Ta)	-25 / +45 °C
Optics	Matt satin symmetric aluminium reflector	Power supply	220-240V 50/60Hz
Flicker	Low flicker	Incandescent wire resistance	850°
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	7 years
Luminous flux maintenance	L80-B20 (50.000h) - L80-B50 (75.000h)	Photobiological safety class	IEC 62471: Exempt group
Beam angle	30°	RAL	7015

CODE

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.
8034		CR		3 = 3000°K		080		EL = standard
				4 = 4000°K		100		LM = 1-10 V
				5 = 5000°K		120		LD = dali
				6 = 6500°K		130		VS = sanded glass
						150		VI = shatterproof glass

ACCESSORIES

AP8034EL - Pole bracket

GP8034 - Protection grid

W-tot	°K	Lm [Tc=25°]	Lm [Output]	A	B	C	Kg	Lamp	Sost.
80	4000	12420	9563	295	100	355	4,9	2 led	150W JM/SAP
100	4000	14163	10905	295	100	355	4,9	2 led	150W JM/SAP
120	4000	18684	14385	295	100	355	4,9	2 led	250W JM/SAP
130	4000	20183	15538	295	100	355	4,9	2 led	250W JM/SAP
150	4000	22315	17180	295	145	355	5,7	2 led	250W JM/SAP

The luminous flux and the system total absorbed power have a tolerance of ± 10% of the given values.

- 3000K = -5,28% lm
- 4000K = standard
- 5000K = +0,90% lm
- 6500K = +3.0% lm

