


T-ZERO^{PRO}

POWER & INNOVATION



REMOTE
telemetry



PEAK
shaving



RENEWABLES
Energy Connection



EASY
handling



BATTERY
technology



SINGLE
phase



LITHIUM
battery



PLUG
& play

Features

Outlet socket	16A 1Ph
Inlet plug	32A 1Ph
Inverter	1x48V/5000VA
Max. Feed through current	1x100A

Lithium Batteries

Battery	51,2VDC -100Ah
Batteries number	3
Battery Pack	51,2 VDC-15 kWh
Expected battery cycle	5000 - 80% DOD

Dimensions & Weight

Dimension	1040 x 1010 x 810 mm
Weight	370 Kg

Distribution Panel

Outlet	16A 1Ph
Inlet	32A 1Ph
Auto start cable connection	Standard
MPPT Solar Charger with RVS Plug	Option

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.

Standard Features

Main circuit breaker & Earth leakage relay
Emergency Stop button
Sides forklift pockets
Lockable control panel
Color Control monitoring display controller
4G GPS antenna & GX GSM module
Remote telemetry

Continuous Inverter Output Power

5000 VA

Overload (0,5 sec)

12500 VA

Running Time with Constant Load from Batteries

2500 VA	6.0 h
---------	-------

Recharging time - Power requested

4.8 h	4.0 kW
-------	--------