SORTIMENTSINFORMATION 02|01

FONTO 8308

Floor socket outlet with with removable and fillable cover, level-adjustable frame, 4×cable outlet

(Levelling support available optionally)



$T \sim c$	hn	ical	l data
166		ıcaı	ı uala

Dimensions (I×w×h): 240×240×95 mm Mounting depth: ca. 95 mm (standard version)

- level-adjustable: 90 - 100 mm - with levelling support: 125 - 165 mm mit threaded pin extension: 125 - 265 mm Material: aluminum natural (salt- and seawater-proof)

IP Protection class:

Deckel:

Verschlussart:

- in closed mode: IP65, suitable for cleaning

with wet sweepers IP20, only dry cleaning - plugged in mode: cover removable snap lock/screw

Cable outlet: yes

Loard capacity: - in closed mode: 2t (20kN) Feed-in cable: 3× back M25

Level-adjustable after installation: yes (+/-6mm) Levelling support: yes (optionally)

Remarks/Features

- Level-adjustable frame (+/- 6 mm) in the offset position for simple adjustment to the finished floor level
- for 8×mounting socket insert 45×45×4mm (e.g. T23, Schuko, RJ45 cat6a, TV, HDMI, USB etc.)
- 6×centre punch marks for additional holes in the bottom of the housing
- suitable for drive-over in close mode

	5		
	\	240 m	1
ca. 125 m –165 mm	ca. 95mm 90-100mm	4	2

Item no.		Description	Equipment
√	840848	FONTO 8308 Floor socket outlet with cover and cable outlet, 240×240×95 mm, closed IP65, aluminium natural, level-adjustable +/- 6 mm	without equipment
√	210647	FONTO 8308 Floor socket outlet with cover and cable outlet, 240×240×95 mm, closed IP65, aluminium natural, level-adjustable +/- 6 mm	8×T23
	210648	FONTO 8308 Floor socket outlet with cover and cable outlet, 240×240×95 mm, closed IP65, aluminium natural, level-adjustable +/- 6 mm	8×Schuko
	210649	FONTO 8308 Floor socket outlet with cover and cable outlet, 240×240×95 mm, closed IP65, aluminium natural, level-adjustable +/- 6 mm	8×British Standard (2×13A)


Other fitting options on request!

Accessories/spare parts

		· · · · · · · · · · · · · · · · · · ·
Item no.		Description
√	154104	FONTO/MASSO Jackscrew levelling support: 1×baseplate and 1×screw M8×60
√	840768	FONTO/MASSO Threaded pin extension M8×160 mm zinc-plated
	840862	FONTO Insertion piece for cable outlet, aluminium natural



- 1. Floor covering
- 2. Floor structure/Screed
- 3. Seal (silicone)
- Stable material (mortar/concrete...)
- 5. 4×cable outlet in cover



Levelling feet are only used for setting the floor socket outlet. load capacity / stability is only obtained by backfilling the floor socket outlet with stable material (mortar, concrete...).

